

ITW GSE

Please contact Patlon: 905-864-8706 | patlon@patlon.com

PRE-CONDITIONED AIR HOSES

PCA Duct with Scuff and Zipper Connections

ITW GSE is the premier supplier of PCA Hoses. The compact and insulated PCA Duct is an extremely flexible heating and air-conditioning duct. It is constructed without wire reinforcement, allowing it to be flattened and rolled when not in use for compact storage. The PCA Duct hose is constructed of a flexible, heavy duty and highly abrasion resistant vinyl coated fabric with moisture proof insulation and a non-rip liner. These flat ducts come with Zippers to easily attach to additional sections to form longer duct assemblies.

Features of ITW GSE PCA Duct:

- Zipper and Velcro connections to allow for longer duct assemblies
- Available with inside diameters of 14"
- Tolerant to temperature variations of -40° F to + 275° F
- · Minimum R-value of 8.0 or greater
- Abrasion resistant scuff strips included

Please contact your Area Sales Manager for details and options.




14" DUCT	LENGTH
AP1410-01	Tapered Adapter
AP1410-03SS	3 Ft. Starter Section
AP1410-10	10 Ft.
AP1410-20	20 Ft.
AP1410-25	25 Ft.
AP1442-03SS	3 Ft. Starter Wire Wound
AP1442-10	10 Ft. Wire Wound
AP1442-20	20 Ft. Wire Wound
AP1442-20SS	20 Ft. Starter Wire Wound









ITW GSE Pre-conditioned Air Hoses

PCA Duct with Zipper Connections

ITW GSE is the premier supplier of PCA Hoses. The compact and insulated PCA Duct is an extremely flexible heating and air-conditioning duct. It is constructed without wire reinforcement, allowing it to be flattened and rolled when not in use for compact storage. The PCA Duct hose is constructed of a flexible, heavy duty and highly abrasion resistant vinyl coated fabric with moisture proof insulation and a non-rip liner. These flat ducts come with Velcro and Zippers to easily attach to additional sections to form longer duct assemblies.

14" DUCT	LENGTH
AP1442-03SS	3 Ft. Starter Section Wire Wound
AP1442-10	10 Ft. Wire Wound
AP1442-20	20 Ft. Wire Wound
AP1442-20SS	20 Ft. Wire Wound Starter
AP1453-01	Tapered Adapter
AP1453-03SS	3 Ft. Starter Section
AP1453-10	10 Ft.
AP1453-20	20 Ft.
AP1453-25	25 Ft.
AP1453-90DEG	3 Ft 90° Bend
AP1453-90DTA	3 Ft 90° Bend Tapered to 8″

Features of ITW GSE PCA Duct:

- Zipper and Velcro connections allow for longer duct assemblies
- Available with inside diameters of 14"
- Tolerant to temperature variations of -40° F to $+275^{\circ}$ F
- Minimum R-value of 8.0 or greater

Please contact your Area Sales Manager for details and options.



