

### **ITW GSE**

Please contact Patlon: 905-864-8706 | patlon@patlon.com

## PREMIUM PRE-**CONDITIONED AIR HOSE**

#### ITW GSE is the premier supplier of PCA Hoses

The compact and insulated Flat Duct is an extremely flexible heating and air-conditioning duct. It is constructed without wire reinforcement, allowing it to be flattened and rolled when not in use for compact storage. The Flat Duct hose is constructed of two-ply, flexible, heavy duty and highly abrasion resistant vinyl coated fabric with moisture proof insulation between the plies and rip stop nylon liner.

Features of ITW GSE Flat Duct:

- Abrasion resistant scuff strip
- · Zipper/Velcro connections allow for longer duct assemblies
- Available with inside diameters of 10", 12" and 14"
- Tolerant to temperature variations of -40° F to + 275° F
- Minimum R-value of 8.0 or greater

The Flat Duct is also available without the abrasion-resistant scuff strip resulting in a lighter weight hose and more compact when stored. This can be advantageous when a longer duct is needed or for use on hose reels.



12" DUCT	14" DUCT	LENGTH
JZ1250-10	JZ1450-10	10 Ft.
JZ1250-20	JZ1450-20	20 Ft.
JZ1250-25	JZ1450-25	25 Ft.



12" DUCT	14" DUCT	LENGTH
JZ1210-10	JZ1410-10	10 Ft.
JZ1210-20	JZ1410-20	20 Ft.
JZ1210-25	JZ1410-25	25 Ft.

Also available are the Wire-Wound Reinforced Ducts. These ducts come insulated or non-

are available to suit your needs. Ducts can be finished with plain cuffs, zippers, Velcro or a combination of finishings.



## ITW GSE Premium Pre-conditioned Air Hose

# ITW GSE offers a variety of Elbows, Tapered Adapters and Support mechanisms for the PC Air Ducts

The Elbows are available in 45° and 90° and insert directly into the duct system allowing for uninterrupted air flow and can be used to bypass obstructions on the ramp.

The JB1562 PCA Hose Support is available in a variety of configurations. Please contact your Area Sales Manager for details and options.









Tapered Adapters also insert directly into the duct system for the final connection to the aircraft connecter. ITW GSE Adapters are available in two styles - straight tapered or 90° tapered.



STRAIGHT TAPERED ADAPTERS		
JZ1210-01	12" taperred to 8"	
JZ1410-01	14" tapered to 8"	



FLAT TAPERED ADAPTERS		
JZ1250-01	12" Tapered To 8"	
JZ1450-01	14" Tapered To 8"	



90° TAPERED ADAPTERS			
JZ1207-90DEG	12" taperred to 8"		
JZ1407-90DEG	14" tapered to 8"		