Global challenges. Innovative solutions.







The Cv International J1O8 offers mobile high and low pressure nitrogen servicing in a robust, CE and ATEX Certified, towable cart configuration.

- Provides 2100 Cu. Ft. of Nitrogen @ 3500 PSI serviceable down to 200 PSI
- High Pressure service from 450-5000 PSI
- Low Pressure service from O-500 PSI
- CE & ATEX Certified
- Four Wheel Running Gear
- Operational testing including Environmental, mobility, vibration & shock including 901D shock test.
- Operating -40 F to + 120 F
- Stored -60 F to + 160 F



Cv International Nitrogen Servicing Cart specifications at a glance.

JIOO Specifications	
Part Number:	903000
Length:	126 Inches
Width:	66 Inches
Height:	55 Inches
Weight: 2700 lbs. Cyl. Empty	
2850 lbs. Cyl. @	3500 psi

J108 Cylinder Specifications

Part Number:	902636
Cylinders Capacity:	4500 PSI
ISO Certification:	9809-2: 2000
Cert. Stamped:	ISO/UN/Pi (TPED)
Weight:	140 Lbs
Output: 350 Cu Ft	of N2 @ 3500 PSI



Patlon Head Office: Patlon Aircraft & Industries Limited • 8130 Fifth Line, Halton Hills, ON, L7G 0B8 • patlon@patlon.com • (905)864-8706

Patlon Ottawa Office: Robert Roy | Business Development Manager • 2068 Robertson Road, Suite 103, Ottawa, ON, K2H 5Y8

E: rroy@pation.com • M: 343-541-8579 • T: 613-828-1424 • www.pation.com