## **ITW GSE**

## PRE-CONDITIONED AIR HOSES

## PCA Duct with Velcro Connections

ITW GSE is the premier supplier of PCA Hoses. The compact and insulated PCA Duct is an extremely flexible heating and air-conditioning duct. It is constructed without wire reinforcement, allowing it to be flattened and rolled when not in use for compact storage. The PCA Duct hose is constructed of a flexible, heavy duty and highly abrasion resistant vinyl coated fabric with moisture proof insulation and a non-rip liner. These flat ducts come with Velcro to easily attach to additional sections to form longer duct assemblies.

Features of ITW GSE Flat Duct:

- Velcro connections allow for longer duct assemblies
- Available with inside diameters of 14"
- Tolerant to temperature variations of -40° F to + 275° F
- Minimum R-value of 8.0 or greater
- · Wire-Wound Reinforced Ducts also available

14" DUCT	DESCRIPTION
AP1483-01*	Tapered Adapter
AP1483-03SS*	3 Ft. Starter Section
AP1483-10*	10 Ft.
AP1483-20*	20 Ft.
AP1483-25*	25 Ft.
AP1483-90DTA	3 Ft 90° Bend Tapered to 8″
AP1483-90DEG	3 Ft 90° Bend
VS1442-03SS	3 Ft. Starter - Wire Wound
VS1442-10	10 Ft. Wire Wound
VS1442-15SS	15 Ft. Starter - Wire Wound
VS1442-20	20 Ft. Wire Wound
VS1442-20SS	20 Ft. Starter - Wire Wound

<sup>\*</sup> Scuff strip not available on the AP1483 series.

Please contact your Area Sales Manager for details and options.







